


# Mitlaufende Zentrierkegel

DIN 228




Typ 8825, Zentrierkegel 60°



Grösse	K MK	Gewicht max.	U/min.	Rundlaufabweichung	Artikel Nr.	A	B	C	D	L
1	1	100	5000	0,008	800002598	20	40,5	35	50	94,0
2	2	180			800002599	30	41,5		60	105,5
2-1		300	800002600		59,0		53	80	123,0	
3	3	350	800002601		67,0	61	100	148,0		
3-1		550	800002602		76,0	70	120	157,0		
3-2		600	800002603		68,5	61	100	171,0		
4	4	700	3000	0,010	800002604	40	68,5	61	100	171,0
4-1					800002605	50	77,5	70	120	180,0
4-2					800002606	70		140		
5	5	750	2000	0,020	800002607	50	70	120	207,0	
5-1					800002608	100	170	207,0		
6					6	2000	1000	0,050	800002609	180


Typ 8882, Zentrierkegel 75°



K MK	d	D	D1	D2	L	Gewicht max.	U/min.	Rundlaufabweichung	Satz	Zentrierkegel	Grundkörper mitlaufend
										Artikel Nr.	
3	80	150	95	56	180	700	4000	0,05	800002954	800002967	800002984
		200	145						800002955	800002968	800002984
4	100	150	95	70	206	1000	3500	0,05	800002956	800002969	800002985
		200	145						800002957	800002970	800002985
		250	195						800002958	800002971	800002985
	125	200	145	95	215	1500	3200		800002959	800002972	800002986
		250	195						800002960	800002973	800002986
		300	245						800002961	800002974	800002986
5	125	200	145	242	245	1800	3000	800002962	-	800002987	
		250	195					800002963	-	800002987	
	160	300	245	800002964	-	800002987					
		250	195	800002965	800002975	800002988					
		300	245	125	245	1800	3000	800002966	800002976	800002988	



Typ 8410, Hydraulik Stirnseitenmitnehmer



Artikel Nr.	D1	K MK	D	D2	D3	A	B	Rundlaufabweichung	Gewicht max.
800002740	27	4	68	12	12	64	80	0,02	55
800002741		5							
800002742	40	4	81	14	67	84	65		
800002743		5							
800002744	50	5	90	20	18	86	113	0,03	100
800002745	63		100						