


Spannbereiche für 2- / 3- / 4-Backenfutter

in Guss und Stahl




Bohr- und Drehbacken

Grösse \varnothing	80	85	100	110	125	140	160
d 1	2-27	2-40	3-33		3-50		3-64
d 2	25-50	32-70	32-62	39-83			50-107
d 3	48-71	62-83	62-93		80-125		98-160
d 4	22-46	22-60	25-56		34-74		42-100
d 5	45-69	54-92	56-87		72-115		94-154



Grösse \varnothing	200	250	315	400	500	630	800
d 1	4-90	5-118	5-131	10-180	20-235	30-335	150-482
d 2	60-145	77-118	90-215	103-272	140-357	180-487	302-634
d 3	130-200	160-250	190-315	230-400	276-500	345-630	468-800
d 4	52-135	62-174	78-200	85-252	120-335	160-465	282-614
d 5	120-202	145-256	172-299	210-380	245-476	325-630	448-780



Harte Grund- und Aufsatzbacken

Grösse \varnothing	125	140	160	200	250
d 1	3-50		3-64	4-90	5-118
d 2	52-96		62-121	72-156	86-197
d 3	95-125		115-160	133-200	160-250
d 4	34-76		42-97	50-130	58-165
d 5	75-118		88-146	105-190	125-235

Grösse \varnothing	315	400	500	630	800
d 1	5-131	10-180	20-235	30-335	150-482
d 2	103-226	127-294	110-400	120-470	240-724
d 3	190-315	230-400	190-500	200-630	316-800
d 4	65-182	72-228	120-410	140-590	252-736
d 5	145-265	165-329	200-485	210-665	328-812