

# Spannzangen COCN

mit doppeltem Innenkonus

Aussen- und Innenspannung möglich



Stahl – Höhe 50 mm

| Grösse $\varnothing$ | Ausführung: Anzahl Schlitze / $\varnothing$ Zentrumbohrung |                     |                     |                     |                     |                     |
|----------------------|--|---------------------|---------------------|---------------------|---------------------|---------------------|
|                      | 4 / $\varnothing$ 0  | 8 / $\varnothing$ 0 | 4 / $\varnothing$ 4 | 4 / $\varnothing$ 8 | 8 / $\varnothing$ 4 | 8 / $\varnothing$ 8 |
| 30                   | S3040H50   | S3080H50            | S3044H50            | S3048H50            | S3084H50            | S3088H50            |
| 40                   | S4040H50   | S4080H50            | S4044H50            | S4048H50            | S4084H50            | S4088H50            |
| 45                   | S4540H50   | S4580H50            | S4544H50            | S4548H50            | S4584H50            | S4588H50            |
| 50                   | S5040H50   | S5080H50            | S5044H50            | S5048H50            | S5084H50            | S5088H50            |
| 60                   | S6040H50   | S6080H50            | S6044H50            | S6048H50            | S6084H50            | S6088H50            |
| 70                   | S7040H50   | S7080H50            | S7044H50            | S7048H50            | S7084H50            | S7088H50            |
| 80                   | S8040H50   | S8080H50            | S8044H50            | S8048H50            | S8084H50            | S8088H50            |



Messing – Höhe 50 mm

| Grösse $\varnothing$ | Ausführung: Anzahl Schlitze / $\varnothing$ Zentrumbohrung |                     |                     |                     |                     |                     |
|----------------------|--|---------------------|---------------------|---------------------|---------------------|---------------------|
|                      | 4 / $\varnothing$ 0  | 8 / $\varnothing$ 0 | 4 / $\varnothing$ 4 | 4 / $\varnothing$ 8 | 8 / $\varnothing$ 4 | 8 / $\varnothing$ 8 |
| 30                   | M3040H50   | M3080H50            | M3044H50            | M3048H50            | M3084H50            | M3088H50            |
| 40                   | M4040H50   | M4080H50            | M4044H50            | M4048H50            | M4084H50            | M4088H50            |
| 50                   | M5040H50   | M5080H50            | M5044H50            | M5048H50            | M5084H50            | M5088H50            |
| 60                   | M6040H50   | M6080H50            | M6044H50            | M6048H50            | M6084H50            | M6088H50            |
| 70                   | M7040H50   | M7080H50            | M7044H50            | M7048H50            | M7084H50            | M7088H50            |
| 80                   | M8040H50   | M8080H50            | M8044H50            | M8048H50            | M8084H50            | M8088H50            |



Stahl – Höhe 55 mm

| Grösse $\varnothing$ | Ausführung: Anzahl Schlitze / $\varnothing$ Zentrumbohrung |                     |                     |                     |                     |                     |
|----------------------|--|---------------------|---------------------|---------------------|---------------------|---------------------|
|                      | 4 / $\varnothing$ 0  | 8 / $\varnothing$ 0 | 4 / $\varnothing$ 4 | 4 / $\varnothing$ 8 | 8 / $\varnothing$ 4 | 8 / $\varnothing$ 8 |
| 30                   | S3040H55   | S3080H55            | S3044H55            | S3048H55            | S3084H55            | S3088H55            |
| 40                   | S4040H55   | S4080H55            | S4044H55            | S4048H55            | S4084H55            | S4088H55            |
| 45                   | S4540H55   | S4580H55            | S4544H55            | S4548H55            | S4584H55            | S4588H55            |
| 50                   | S5040H55   | S5080H55            | S5044H55            | S5048H55            | S5084H55            | S5088H55            |
| 60                   | S6040H55   | S6080H55            | S6044H55            | S6048H55            | S6084H55            | S6088H55            |
| 70                   | S7040H55   | S7080H55            | S7044H55            | S7048H55            | S7084H55            | S7088H55            |
| 80                   | S8040H55   | S8080H55            | S8044H55            | S8048H55            | S8084H55            | S8088H55            |



Stahl – Höhe 40 mm

| Grösse $\varnothing$ | Ausführung: Anzahl Schlitze / $\varnothing$ Zentrumbohrung |                     |                     |                     |                     |                     |
|----------------------|--|---------------------|---------------------|---------------------|---------------------|---------------------|
|                      | 4 $\varnothing$ 0  | 8 / $\varnothing$ 0 | 4 / $\varnothing$ 4 | 4 / $\varnothing$ 8 | 8 / $\varnothing$ 4 | 8 / $\varnothing$ 8 |
| 40                   | S4040H40   | S4080H40            | S4044H40            | S4048H40            | S4084H40            | S4088H40            |
| 50                   | S5040H40   | S5080H40            | S5044H40            | S5048H40            | S5084H40            | S5088H40            |
| 60                   | S6040H40   | S6080H40            | S6044H40            | S6048H40            | S6084H40            | S6088H40            |

Achtung: nur mit Druckstücken für Höhe 40 mm einsetzbar!

Sonder auf Wunsch

